

# Analogue cameras

SuperLoLux™

		CCD	TV lines	Lens	Easy or True Day Night	Lux level (colour/B&W)	Vandal resistant	IP Rating	Privacy masking	Auto tracking	MTBF	Other information
TK-C9200E/ TK-C9201EG		1/3"	600	N/A	Easy	0.025/ 0.015	N/A	N/A	4 areas	N/A	93,000	3D Noise Reduction Focus Adjustment Digital zoom capability 14-bit DSP
TK-C9300E/ TK-C9301EG		1/3"	600	N/A	True	0.025/ 0.003	N/A	N/A	4 areas	N/A	93,000	3D Noise Reduction ExDR function Focus Adjustment 14-bit DSP
TK-C9510E/ TK-C9511EG		1/2"	600	N/A	True	0.05/ 0.006	N/A	N/A	4 areas	N/A	77,000	3D Noise Reduction 14-bit DSP Anti Fog Mode
TK-WD310E(B)		1/3" WDR	480	N/A	Easy	1.9/ 0.5	N/A	N/A	No	N/A	96,000	14-bit DSP automatic 5 levels exposure control
TK-C2201E		1/3"	600	3.7x 2.8 - 10.5mm	Easy	0.025/ 0.015	Yes	N/A	4 areas	N/A	90,000	3D Noise Reduction Fine Focus 14-bit DSP
TK-C2201WPE		1/3"	600	3.7x 2.8 - 10.5mm	True	0.025/ 0.003	Yes	IP66	4 areas	N/A	90,000	3D Noise Reduction Fine Focus 14-bit DSP
TK-C685E		1/4"	540	27x zoom 3.43 - 92.6mm	True	0.5/ 0.04	N/A	N/A	8 areas	Yes	57,000	ExDR function Direct Drive One-Touch Lock
TK-C686E(A)		1/4"	540	36x zoom 3.43 - 122mm	True	0.5/ 0.04	N/A	N/A	8 areas	Yes	57,000	ExDR function Image Stabilizer Direct Drive
TK-C685WPE		1/4"	540	27x zoom 3.43 - 92.6mm	True	0.5/ 0.04	N/A	IP66	8 areas	Yes	52,000	ExDR function Direct Drive
TK-C686WPE(C)		1/4"	540	36x zoom 3.43 - 122mm	True	0.5/ 0.04	N/A	IP66	8 areas	Yes	52,000	ExDR function Image Stabilizer Direct Drive


[www.jvcpro.eu](http://www.jvcpro.eu)

JVC is a trademark or registered trademark of Victor Company of Japan, Limited.  
E&OE. Design and specifications subject to change without notice. NVR-2010.

**JVC**  
The Perfect Experience

# Network cameras



		CCD Progressive	Image Size	Lens	Easy or True Day Night	PoE	Streaming	Vandal resistant	Vandal proof	Privacy masking	Auto tracking	MTBF	Other information
VN-V25U		1/4"	VGA	C/CS	Easy	Yes	Dual MPEG-4/ M-JPEG	N/A	N/A	Free shape/ unlimited	N/A	44,000	-
VN-V26U		1/4"	VGA	C/CS	True	Yes	Dual MPEG-4/ M-JPEG	N/A	N/A	Free shape/ unlimited	N/A	42,000	Bi-directional audio support
VN-X35U		1/3"	1.3 MP	C/CS	Easy	Yes	Dual MPEG-4/ M-JPEG	N/A	N/A	Free shape/ unlimited	N/A	43,000	Bi-directional audio support
VN-V225U		1/4"	VGA	Built-in 3.8x variable focal length, auto iris	True	Yes	Dual MPEG-4/ M-JPEG	Yes	-	Free shape/ unlimited	N/A	90,000	Bi-directional audio support
VN-V225VPU		1/4"	VGA	Built-in 3.8x variable focal length, auto iris	True	Yes	Dual MPEG-4/ M-JPEG	-	Yes	Free shape/ unlimited	N/A	90,000	Bi-directional audio support, IP66 weather rating, optional heater
VN-X235U		1/3"	1.3 MP	Built-in 3.0x variable focal length, auto iris	True	Yes	Dual MPEG-4/ M-JPEG	Yes	-	Free shape/ unlimited	N/A	90,000	Bi-directional audio support
VN-X235VPU		1/3"	1.3 MP	Built-in 3.0x variable focal length, auto iris	True	Yes	Dual MPEG-4/ M-JPEG	-	Yes	Free shape/ unlimited	N/A	90,000	Bi-directional audio support, IP66 weather rating, optional heater
VN-V685U		1/4"	VGA	27x optical zoom lens (32x digital)	True	Yes	Dual MPEG-4/ M-JPEG	N/A	N/A	8 areas	Yes	52,000	Direct drive mechanism, image stabiliser, 3D noise reduction
VN-V686BU(A)		1/4"	VGA	36x optical zoom lens (32x digital)	True	Yes	Dual MPEG-4/ M-JPEG	N/A	N/A	8 areas	Yes	52,000	Direct drive mechanism, image stabiliser, 3D noise reduction
VN-V686WPBU(A)		1/4"	VGA	36x optical zoom lens (32x digital)	True	Yes, heater not powered	Dual MPEG-4/ M-JPEG	-	Yes	8 areas	Yes	48,000	Direct drive mechanism, image stabiliser, 3D noise reduction, IP66 weather rating, housing with wall mount arm

[www.jvcpro.eu](http://www.jvcpro.eu)

JVC is a trademark or registered trademark of Victor Company of Japan, Limited.  
E&OE. Design and specifications subject to change without notice. NVR-2010.

**JVC**  
The Perfect Experience